

IN THE CLAIMS

1. (Currently Amended) A soft-reference magnetic memory digitizing device comprising:
 - an array of soft-reference magnetic memory cells, each having at least one ferromagnetic sense layer characterized by an alterable orientation of magnetization, the orientation changing upon a ~~the~~ substantially proximate application of at least one externally-applied magnetic field as applied by a magnetically tipped stylus.

2. (Currently Amended) A soft-reference magnetic memory digitizing device comprising:
 - an array of soft-reference magnetic memory cells, each having at least one ferromagnetic sense layer characterized by an alterable orientation of magnetization, the orientation changing upon a ~~the~~ substantially proximate application of at least one externally-applied magnetic field; and
 - at least one magnetically tipped stylus for applying at least one external magnetic field to at least one magnetic memory cell of the array.

3. (Currently Amended) The soft-reference digitizer of claim 2, further comprising a display operable to display information, the display coupled to the array of magnetic memory cells such that the orientation of a given memory cell is used locally within the display to determine the information displayed upon the display proximate to the given memory cell.

4. (Currently Amended) A soft-reference magnetic memory digitizing device comprising:
 - an array of soft-reference magnetic memory cells, each memory cell including:
 - at least one ferromagnetic sense layer characterized by an alterable orientation of magnetization, the orientation changing upon a ~~the~~ substantially proximate application of at least one externally-applied magnetic field;
 - at least one ferromagnetic soft-reference layer having a non-pinned orientation of magnetization; and
 - at least one intermediate layer forming a magnetic tunnel junction between the sense layer and the soft-reference layer,
 - wherein the alterable orientation of the sense layer is not substantially affected by the soft-reference layer; and
 - at least one magnetically tipped stylus for applying at least one external magnetic field to at least one magnetic memory cell of the array.

5. (Original) The soft-reference digitizer of claim 4, wherein the sense layer has a higher coercivity than the soft-reference layer.
6. (Original) The soft-reference digitizer of claim 4, wherein the magnetic tip of the stylus is a permanent magnet.
7. (Original) The soft-reference digitizer of claim 4, wherein the magnetic tip of the stylus is a current-carrying coil.
8. (Currently Amended) The soft-reference digitizer of claim 4, further comprising a display operable to display information, the display coupled to the array of magnetic memory cells such that the orientation of a given sense layer is used locally within the display to determine the information displayed upon the display proximate to the given sense layer.
9. (Original) The soft-reference digitizer of claim 4, further comprising a display characterized by an array of pixels, the display at least partially integrated with the array of magnetic memory cells, each memory cell further being coupled to at least one pixel.
10. (Currently Amended) A soft-reference magnetic memory digitizing device comprising:
 - a plurality of magnetic memory cells, each memory cell including:
 - at least one ferromagnetic sense layer characterized by an alterable orientation of magnetization, the orientation changing upon a ~~the~~ substantially proximate application of at least one externally-applied magnetic field;
 - an intermediate layer in contact with the sense layer; and
 - at least one ferromagnetic soft-reference layer having a non-pinned orientation of magnetization; the reference layer in contact with the intermediate layer, opposite from the sense layer,
 - wherein the alterable orientation of the sense layer is not substantially affected by the soft-reference layer; and
 - at least one magnetically tipped stylus for applying at least one external magnetic field to at least one magnetic memory cell of the array.
11. (Original) The soft-reference digitizer of claim 10, wherein the sense layer has a higher coercivity than the soft-reference layer.
12. (Original) The soft-reference digitizer of claim 10, wherein the magnetic tip of the stylus is a permanent magnet.

13. (Original) The soft-reference digitizer of claim 10; wherein the magnetic tip of the stylus is a current-carrying coil.
14. (Currently Amended) The soft-reference digitizer of claim 10, further comprising a display operable to display information, the display coupled to the array of magnetic memory cells such that the orientation of a given sense layer is used locally within the display to determine the information displayed upon the display proximate to the given sense layer.
15. (Original) The soft-reference digitizer of claim 10, further comprising a display characterized by an array of pixels, the display at least partially integrated with the array of magnetic memory cells, each memory cell further being coupled to at least one pixel.
16. (Currently Amended) A method of using a soft-reference magnetic memory digitizing device comprising:
 providing an array of soft-reference magnetic memory cells, each characterized by a sense layer having an alterable orientation of magnetization and a soft-reference layer, the orientation of the sense layer changing upon a ~~the~~ substantially proximate application of at least one externally-applied magnetic field; and
 applying an external magnetic field to at least a portion of the array to change the magnetic orientation of at least one memory cell;
 reading the array by applying a sense current to the magnetic memory cells and reading a ~~the~~ resistance of each cell, the sense current also sufficient to establish a magnetic field to orient the soft-reference layer during the read operation; and
 refreshing the array by applying a refresh current sufficient to align substantially all the memory cells to a predetermined orientation.
17. (Original) The method of claim 16, further including initializing the array by applying an initialize current sufficient to align substantially all the sense layers to a predetermined orientation.
18. (Original) The method of claim 16, further comprising displaying an image upon a display, the image corresponding to the applied external magnetic field as determined by the resistance of each cell within the array.
19. (Original) The method of claim 18, wherein the display is comprised of an array of pixels, the display at least partially integrated with the array of magnetic memory cells, each memory cell further being coupled to at least one pixel.

20. (Currently Amended) The method of claim 16, wherein ~~the condition of~~ the digitizing device continuously cycles between a reading and a refreshing state.
21. (Currently Amended) A method of using a soft-reference magnetic memory digitizing device having an array of magnetic memory cells, each memory cell characterized by at least one ferromagnetic sense layer characterized by an alterable orientation of magnetization, the orientation changing upon a ~~the~~ substantially proximate application of at least one externally-applied magnetic field; and at least one ferromagnetic soft-reference layer having a non-pinned orientation of magnetization; wherein the alterable orientation of the sense layer is not substantially affected by the soft-reference layer, the method comprising:
- applying an external magnetic field to at least a portion of the array to change the magnetic orientation of at least one sense layer;
- reading the array by applying a sense current to the magnetic memory cells and reading a ~~the~~ resistance of each cell, the sense current also sufficient to establish a magnetic field to orient the soft-reference layer during the read operation; and
- refreshing the array by applying a refresh current sufficient to generate a re-fresh magnetic field sufficient to align substantially all the sense layers to a predetermined orientation.
22. (Original) The method of claim 21, further including initializing the array by applying an initialize current sufficient to align substantially all the sense layers to a predetermined orientation.
23. (Original) The method of claim 21, further comprising displaying an image upon a display, the image corresponding to the applied external magnetic field as determined by the resistance of each cell within the array.
24. (Original) The method of claim 23, wherein the display is comprised of an array of pixels, the display at least partially integrated with the array of magnetic memory cells, each memory cell further being coupled to at least one pixel.
25. (Currently Amended) The method of claim 21, wherein ~~the condition of~~ the digitizing device continuously cycles between a reading and a refreshing state.

26. (Currently Amended) A method of using a soft-reference magnetic memory digitizing device comprising:
- providing an array of magnetic memory cells, each memory cell including:
 - at least one ferromagnetic sense layer characterized by an alterable orientation of magnetization, the orientation changing upon ~~a~~ the-substantially proximate application of at least one externally-applied magnetic field;
 - an intermediate layer in contact with the sense layer; and
 - at least one ferromagnetic soft-reference layer having a non-pinned orientation of magnetization; the reference layer in contact with the intermediate layer, opposite from the sense layer;
 - wherein the alterable orientation of the sense layer is not substantially affected by the soft-reference layer;
 - applying an external magnetic field to at least a portion of the array to change the magnetic orientation of at least one sense layer;
 - reading the array by applying a sense current to the magnetic memory cells and reading ~~a~~ the-resistance of each cell, the sense current also sufficient to establish a magnetic field to orient the soft-reference layer during the read operation; and
 - refreshing the array by applying a refresh current sufficient to generate a re-fresh magnetic field sufficient to align substantially all the sense layers to a predetermined orientation.
27. (Original) The method of claim 25, further including initializing the array by applying an initialize current sufficient to align substantially all the sense layers to a predetermined orientation.
28. (Original) The method of claim 25, further comprising displaying an image upon a display, the image corresponding to the applied external magnetic field as determined by the resistance of each cell within the array.
29. (Original) The method of claim 28, wherein the display is comprised of an array of pixels, the display at least partially integrated with the array of magnetic memory cells, each memory cell further being coupled to at least one pixel.
30. (Original) The method of claim 25, wherein ~~the condition of~~ the digitizing device continuously cycles between a reading and a refreshing state.

31. (Currently Amended) A soft-reference magnetic memory digitizing device comprising:
- an encasing outer surface;
 - an array of soft-reference magnetic memory cells encased within and disposed below the outer surface, each characterized by an alterable orientation of magnetization, the orientation changing upon a ~~the~~ substantially proximate application of at least one externally-applied magnetic field; and
 - a magnetically tipped stylus external to the encasing outer surface, the stylus operable to apply at least one external magnetic field to at least one magnetic memory cell of the array.
32. (Currently Amended) The soft-reference magnetic memory digitizing device of claim 31, wherein each soft-reference magnetic memory cell of the array comprises:
- at least one ferromagnetic sense layer characterized by an alterable orientation of magnetization, the orientation changing upon a ~~the~~ substantially proximate application of the least one externally-applied magnetic field;
 - at least one ferromagnetic soft-reference layer having a non-pinned orientation of magnetization, wherein the alterable orientation of the sense layer is not substantially affected by the soft-reference layer; and
 - at least one intermediate layer forming a magnetic tunnel junction between the sense layer and the soft-reference layer.
33. (Previously Added) The soft-reference digitizer of claim 32, wherein the sense layer has a higher coercivity than the soft-reference layer.
34. (Currently Amended) The soft-reference digitizer of claim 32, further comprising a display operable to display information, the display coupled to the array of magnetic memory cells such that the orientation of a given sense layer is used locally within the display to determine the information displayed upon the display proximate to the given sense layer.